Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-479-8083

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.125 inches

Overall Height:

1.781 inches

Overall Width:

1.781 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.437 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Distance De

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.531 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

61-3 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

Polarization Method:

Contact to contact polarizing keys

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Compression nut

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Rubber single mating end



Terminal Type: Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 49 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.053 gold grains, troy and 0.053 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0