

View Online at <https://aerobasegroup.com/nsn/5935-00-480-4977>

Body Style:

Straight shape, internal coupling

Overall Length:

1.684 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Weather resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Bnc all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

10000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

End Application:

Smissile, mx peacekeeper; general purpose electronic test equipment gpete; instrument landing system an/grn-2 (v); whidbey island class lsd; support equipment, mx peacekeeper missile; ticonderoga class cg (47) ; tarawa class lha

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic all mating ends

Criticality Code Justification:

Feat

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0