## NSN 5935-00-480-5114

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-480-5114 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.800 inches **Overall Height:** Between 1.120 inches and 1.130 inches **Overall Width:** Between 1.120 inches and 1.130 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.901 inches and 0.911 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.901 inches and 0.911 inches **Distance From Mounting Shoulder To Front Face:** Between 0.375 inches and 0.385 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.938 inches **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Anodize

**Shell Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

## NSN 5935-00-480-5114

Receptacle Dummy Connector - Page 2 of 2



Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.