## NSN 5935-00-480-5476

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-480-5476

**Body Style:** 

Straight shape, external coupling

**Overall Height:** 

1.453 inches

**Overall Width:** 

1.453 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 

1.156 inches

**Distance From Mounting Shoulder To Front Face:** 

0.587 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

20-16 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

20.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

0.0

Shell Type:

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Rubber fluorosilicone class fq single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## NSN 5935-00-480-5476

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type:  |
|---|
| Crimp single mating end single contact grouping                       |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium   |
| Shell Surface Treatment Specification:                                |
| Qq-p-416 type 2, cl 3 federal specification single treatment response |
| Shell Material Specification:   |
| Qq-a-591 federal specification single material response               |
| Included Contact Quantity:  |
| 16 single mating end single contact grouping                          |
| Included Contact Type:  |
| Round socket single mating end single contact grouping                |
| Precious Material And Location:                                       |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.016 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-g-45204 spec.   |