# NSN 5935-00-481-0043

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-481-0043

# Body Style:

Straight shape, internal coupling

## **Overall Length:**

1.513 inches

# **Overall Diameter:**

0.750 inches

## **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

8-33 single mating end

## Contact Removability:

Removable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### **Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end single contact grouping

## Polarization Method:

Keyway or multiple keyway

## Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet latch

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Rubber single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# **Included Contact Quantity:**

3 single mating end single contact grouping

NSN 5935-00-481-0043

Electrical Plug Connector - Page 2 of 2



#### Included Contact Type:

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.003 gold grains, troy

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-26482 government specification

Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0