## NSN 5935-00-481-0381

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-481-0381 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Overall Height:** 0.803 inches **Overall Width:** 1.531 inches **Unthreaded Mounting Hole Diameter:** 0.136 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 120 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 8.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Post jacksocket Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

. . . .

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## NSN 5935-00-481-0381

Electrical Receptacle Connector - Page 2 of 2



| Insert Material:   |
|--|
| Plastic diallyl phthalate glass filled single mating end                               |
| Terminal Type:   |
| Wire wrap single mating end single contact grouping                                    |
| Guide Design And Location:   |
| Key shape socket right-hand at 3 oclock  |
| Insert Material Specification:   |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity:   |
| 120 single mating end single contact grouping  |
| Included Contact Type:   |
| Hermaphrodite single mating end single contact grouping                                |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.120 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |
| Mil-m-14 spec.   |