## NSN 5935-00-481-4104

Thread Class: 2a and 2b

**Body Style:** 

**Thread Direction:** 

Right-hand and right-hand

Angle shape, w/o cable clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-481-4104

**Overall Diameter:** Between 2.000 inches and 2.032 inches **Body Angle In Deg:** 90.0 **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Fk-w20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Distance From Centerline To Connector End:** Between 1.828 inches and 1.922 inches **Distance From Centerline To Cable End:** Between 1.453 inches and 1.485 inches Thready Qty Per Inch (tpi): 18 and 6 **Thread Size:** 1.750 inches and 1.812 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping

## **NSN 5935-00-481-4104**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.020 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0