NSN 5935-00-481-4968

Thread Class:

Copper alloy

Thread Direction:

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-481-4968

Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
0.490 inches
Overall Height:
0.480 inches
Cable Entrance Diameter:
0.074 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Connector Locking Method: Internally threaded coupling nut
_
Internally threaded coupling nut
Internally threaded coupling nut Connector Cable Strain Relief Method:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi):
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Internally threaded coupling nut Connector Cable Strain Relief Method: Cable clamp Thready Qty Per Inch (tpi): 40 Thread Size: 0.138 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end

NSN 5935-00-481-4968Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Gold
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact @and shell surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0