Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-481-7796

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.531 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.145 inches and 0.151 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.370 inches and 1.380 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.370 inches and 1.380 inches
Distance From Mounting Shoulder To Front Face:
Between 0.812 inches and 0.822 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24-80 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 23 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.023 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0