Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-482-0282

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Height:
Between 1.323 inches and 1.363 inches
Overall Width:
Between 1.323 inches and 1.363 inches
Environmental Protection:
Moisture resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
18
Thread Size:
1.063 inches
Terminal Location:
Back single mating end single contact grouping



Contact Mater	
	ingle mating end single contact grouping
Contact Surfa	
-	ting end single contact grouping
Insert Materia	
	single mating end
	ce Treatment Specification:
	pe 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type	
	ating end single contact grouping
Shell Material	
Aluminum alloy	
Shell Surface	Treatment:
Nickel	
Included Cont	act Quantity:
8 single mating	gend single contact grouping
Included Cont	act Type:
Round socket s	single mating end single contact grouping
Precious Mate	erial And Location:
Contact surface	e gold
Precious Mate	erial And Weight:
0.008 gold grai	ns, troy
Precious Mate	erial:
Gold	
Thread Series	Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Measu	ire:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (milita	ry Standard):
Mil-g-45204 sp	ec.