

View Online at <https://aerobasegroup.com/nsn/5935-00-482-3788>

**Body Style:**

Straight shape w/o clamp

**Overall Height:**

4.719 inches

**Overall Diameter:**

2.031 inches

**Environmental Protection:**

Corrosion resistant and shock resistant and vibration resistant

**Cable Entrance Diameter:**

0.595 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

20.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Locking Method:**

Contact twistlock

**Connector Cable Strain Relief Method:**

Cord grip

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Screw single mating end all contact groupings

**Shell Material:**

Plastic

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Included Contact Type:**

Curved pin w/lock single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.004 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.