# NSN 5935-00-482-5082

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-482-5082

#### **Body Style:**

Straight shape, internal coupling

#### **Overall Length:**

1.375 inches

## **Overall Diameter:**

1.375 inches

### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

"18-8, 22-404" single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### Polarization Method:

Key, multiple key groove

# Insert Position In Deg:

238.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet latch

### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### Insert Material:

Rubber silicone class q single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204 type 2 cl 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

#### Included Contact Quantity:

8 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

Electrical Plug Connector - Page 2 of 2



**Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.008 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.