

View Online at <https://aerobasegroup.com/nsn/5935-00-482-5127>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.275 inches

Overall Height:

1.688 inches

Overall Width:

1.688 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.155 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.292 inches and 1.302 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.292 inches and 1.302 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

20-39 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches

Thread Size:

1.188 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

37 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.039 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3472 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.