

View Online at <https://aerobasegroup.com/nsn/5935-00-482-6057>

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.726 inches

Overall Height:

0.932 inches

Overall Width:

0.655 inches

Environmental Protection:

Salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.133 inches

Distance Between Mounting Facility Centers:

Between 2.411 inches and 2.421 inches

Board Accommodated Length:

1.945 inches and 1.955 inches single board

Board Accommodated Width:

Between 0.071 inches and 0.081 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Switching contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Unable To Decode:

Unable to decode and unable to decode

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

30 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Test Data Document:

18876-10243528 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.