NSN 5935-00-483-4026

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-483-4026

Body Style: Straight shape **Overall Length:** Between 2.714 inches and 2.744 inches **Overall Height:** 0.648 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.495 inches and 2.505 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:**

Cadmium

Insert Material Specification:

Mil-m-19833, type qdi-30f military specification single material response single mating end

NSN 5935-00-483-4026

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.037 gold grains, troy and 0.037 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.