

View Online at <https://aerobasegroup.com/nsn/5935-00-483-4101>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.198 inches and 1.208 inches

Overall Diameter:

Between 0.422 inches and 0.452 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

10-6 all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.010 gold grains, troy and 0.110 silver grains, troy

Precious Material:

Gold and silver

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0