

View Online at <https://aerobasegroup.com/nsn/5935-00-483-4259>

**Body Style:**

Straight shape, flange mount, external coupling

**Overall Length:**

1.640 inches

**Overall Height:**

1.302 inches

**Overall Width:**

1.302 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.104 inches and 0.136 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.952 inches and 0.984 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.952 inches and 0.984 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.510 inches and 0.542 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

27-2 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Potting

**Connector Locking Method:**

Ball

**Connector Cable Strain Relief Method:**

Potting type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-26482 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0