

View Online at <https://aerobasegroup.com/nsn/5935-00-484-1291>

Body Style:

Straight shape w/screw locks

Overall Length:

1.250 inches

Overall Height:

0.344 inches

Overall Width:

0.906 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20 20-20 single mating end

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Screw lock pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Reference Number Differentiating Characteristics:

As differentiated by navord od41152

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.