## NSN 5935-00-484-3101

Right-hand and right-hand and right-hand

Anodize and dichromate potassium

2b and 2b and 2a

Thread Direction:



Electrical Receptacle Connector Body - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-484-3101

Thread Class:

Body Style:
Straight shape, rectangular
Overall Length:
0.730 inches
Overall Height:
1.860 inches
Overall Width:
2.875 inches
Environmental Protection:
Pressure proof and pressure proof
Unthreaded Mounting Hole Diameter:
0.149 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.500 inches
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
15
Contact Position Arrangement Style:
158 single mating end
Polarization Method:
Polarization boss and jackscrew
Shell Type:
Solid
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
28 and 32
Thread Size:
0.250 inches and 0.164 inches
Insert Material:
Plastic diallyl phthalate single mating end and plastic diallyl phthalate single mating end
Shell Material:
Stainless steel
Shell Surface Treatment:

## NSN 5935-00-484-3101

Electrical Receptacle Connector Body - Page 2 of 2



Insert Material Specification
-------------------------------

Mil-p-19833, type gdi-30f military specification single material response single mating end

**Thread Series Designator:** 

Unf and unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.