Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-484-3191

Overall Height:2.640 inchesOverall Width:1.734 inchesBody Length:1.350 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingPolarization Method:Nating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Rouper alloy single mating end single contact groupingFerminal Location:Back single mating end single contact groupingContact Material:Rubber synthetic single mating end single contact grouping
Overall Width:1.734 inchesBody Length:1.350 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingPolarization Method:Mating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping
1.734 inchesBody Length:1.350 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 2nd contact groupingPolarization Method:Nating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingForminal Location:Back single mating end single contact groupingContact Material:Rouper alloy single mating end single contact grouping
Body Length:1.350 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Mating endShell Type:SolidContact Mating end single contact groupingContact Mating end single contact groupingPolarization Method:Mating endShell Type:SolidContact Material:Copper alloy single mating end single contact groupingContact Material:Rubber synthetic single mating end
1.350 inchesEnvironmental Protection:Moisture resistant and salt water resistant and vibration resistantUnthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Nating endShell Type:SolidContact Material:Copper alloy single mating end single contact groupingForminal Location:Back single mating end single contact groupingContact Material:Rouper alloy single mating end single contact groupingPolarizetionBack single mating end single contact groupingContact Material:Rouper alloy single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Material:Copper synthetic single mating endSingle mating end single contact groupingContact Material:Contact Single mating end Single contact grouping<
Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 1.921 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Moisture resistant and salt water resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.112 inches Distance Between Mounting Facility Centers: 1.921 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Katerial: Rubber synthetic single mating end
Unthreaded Mounting Hole Diameter:0.112 inchesDistance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Mating endShell Type:SolidContact Material:Copper alloy single mating end single contact groupingContact Material:Rubber synthetic single mating end
0.112 inches Distance Between Mounting Facility Centers: 1.921 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Distance Between Mounting Facility Centers:1.921 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Mating endShell Type:SolidContact Material:Copper alloy single mating end single contact groupingRubber synthetic single mating end
 1.921 inches Mating End Quantity: Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Mating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Mating endShell Type:SolidContact Material:Copper alloy single mating end single contact groupingInsert Material:Rubber synthetic single mating end
1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Rubber synthetic single mating end
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end 3rd contact groupingContact Maximum Ac Voltage Rating In Volts:750.0 single mating end 2nd contact groupingPolarization Method:Mating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Rubber synthetic single mating end
 Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Contact Maximum Current Rating In Amps: 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
 7.5 single mating end 3rd contact grouping Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Contact Maximum Ac Voltage Rating In Volts: 750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
750.0 single mating end 2nd contact grouping Polarization Method: Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Polarization Method:Mating endShell Type:SolidTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingInsert Material:Rubber synthetic single mating end
Mating end Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Shell Type: Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Solid Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Contact Material: Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Copper alloy single mating end single contact grouping Insert Material: Rubber synthetic single mating end
Insert Material: Rubber synthetic single mating end
Rubber synthetic single mating end
Terminal Type
i oi minur i ypo.
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
-
8 single mating end 2nd contact grouping
-
8 single mating end 2nd contact grouping
8 single mating end 2nd contact grouping Included Contact Type:

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0