NSN 5935-00-484-3636

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-484-3636 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.562 inches **Overall Height:** 0.797 inches **Overall Width:** 0.438 inches **Distance Between Mounting Facility Centers:** 1.250 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1700.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thread Length: 0.266 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-484-3636

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0