# NSN 5935-00-484-3637

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-484-3637

**Thread Class:** 

2a and 2b and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.220 inches and 1.280 inches

**Overall Height:** 

0.797 inches

Overall Width:

Between 0.410 inches and 0.470 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and corrosion resistant

**Distance Between Mounting Facility Centers:** 

0.937 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

13.0 single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic melamine mineral filled single mating end

# NSN 5935-00-484-3637

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

# **Included Contact Quantity:**

14 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.014 gold grains, troy

#### **Precious Material:**

Gold

# **Thread Series Designator:**

Unc and unc and unc

#### **Specification Data:**

18876-10224814 manufacturers specification control

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.