

View Online at <https://aerobasegroup.com/nsn/5935-00-484-5056>

**Body Style:**

Straight shape threaded

**Overall Length:**

0.812 inches

**Overall Diameter:**

1.312 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Distance From Mounting Shoulder To Front Face:**

0.675 inches

**Mounting Facility Thickness:**

0.108 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

27-30 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

30.0 and 120.0 and 210.0 and 285.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Insert Material:**

Plastic single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response

**Shell Material Specification:**

Mil-c-26482 military specification single material response

**Insert Material Specification:**

Mil-m-14, ty mfh military specification single material response single mating end

**Special Features:**

Solder flange mounted

**Test Data Document:**

03640-6094301 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.