## NSN 5935-00-484-5064

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-484-5064 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.813 inches **Overall Diameter:** 1.062 inches **Environmental Protection:** Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant **Distance From Mounting Shoulder To Front Face:** 0.675 inches **Mounting Facility Thickness:** 0.108 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 12-14 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Spring friction Thready Qty Per Inch (tpi): 20 **Thread Size:** 

0.812 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-00-484-5064

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Shell Material Specification:** Qq-a-591 federal specification single material response **Insert Material Specification:** Mil-m-14, ty mfh military specification single material response single mating end **Included Contact Quantity:** 37 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.037 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef **Specification Data:** 03640-6083818 manufacturers specification control Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-m-14 spec.