# NSN 5935-00-484-5075

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-484-5075

## Body Style:

Straight shape, internal coupling

#### **Overall Length:**

0.813 inches

### **Overall Diameter:**

1.352 inches

#### **Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

27-30 single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

150.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Spring friction

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Rubber silicone class q single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Included Contact Quantity:

91 single mating end single contact grouping

NSN 5935-00-484-5075

Electrical Plug Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.091 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.