

View Online at <https://aerobasegroup.com/nsn/5935-00-484-5123>

**Body Material:**

Plastic

**Body Style:**

Top mount

**Fabrication Method:**

Molded

**Overall Length:**

Between 1.328 inches and 1.360 inches

**Temperature Rating:**

-65.0 degrees celsius and 120.0 degrees celsius

**Overall Height:**

0.688 inches

**Overall Width:**

Between 0.385 inches and 0.395 inches

**Mounting Hole Diameter:**

Between 0.122 inches and 0.127 inches

**Body Mounting Hole Accommodation Length:**

0.820 inches

**Body Mounting Hole Accommodation Width:**

Between 0.400 inches and 0.410 inches

**Distance Between Mounting Facility Centers:**

Between 1.073 inches and 1.083 inches

**Mounting Hole Style:**

Rectangular, w/two mounting holes/slots

**Specific Equipment Accommodated:**

Relay

**Contact Maximum Current Rating In Amps:**

3.0

**Contact Material:**

Phosphor bronze

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

8

**Polarization Type:**

Colored dot

**Projection Length Above Mounting Surface:**

0.469 inches

**Mounting Method:**

Body through hole

**Mounting Type For Which Designed:**

Chassis

**Features Provided:**

Component retaining device

**Contact Position Arrangement Style:**

Dual in line

**Contact Maximum Voltage In Volts And Current Type:**

2700.0 ac and 2700.0 dc

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.008 gold grains, troy and 0.008 silver grains, troy

**Precious Material:**

Gold and silver

**Terminal Type And Quantity:**

8 solder well

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300