NSN 5935-00-485-4991

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-485-4991

Body Style:

Straight shape

Overall Length:

Between 2.714 inches and 2.744 inches

Overall Height:

0.683 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Vibration resistant and shock resistant and moisture resistant and corrosion resistant and salt spray proof

Unthreaded Mounting Hole Diameter:

Between 0.086 inches and 0.091 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

21 single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 140.0 degrees celsius

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold and copper single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class i military specification 1st treatment response and mil-g-45204, type i military specification 1st treatment response and mil-c-14550, class 4 military specification 2nd treatment response single mating end 1st contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-485-4991 Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Shell Material Specification:
Qq-s-698, temper t5 federal specification single material response
nsert Material Specification:
Mil-p-19833, type gdi-30f military specification single material response single mating end
ncluded Contact Quantity:
17 single mating end 1st contact grouping
ncluded Contact Type:
Round socket single mating end 1st contact grouping
Special Features:
Float mount
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.017 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0
Mil-std (military Standard):
Mil-g-45204 spec.