

View Online at <https://aerobasegroup.com/nsn/5935-00-485-5018>

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.680 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Vibration resistant and shock resistant and moisture resistant and corrosion resistant and salt spray proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

36w4 single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -55.0 degrees celsius and 140.0 degrees celsius

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold and copper single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class i military specification 1st treatment response and mil-g-45204, type i military specification 1st treatment response and mil-c-14550, class 4 military specification 2nd treatment response single mating end 1st contact grouping

Terminal Type:

Solder well single mating end 1st contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type gdi-30f federal specification all treatment responses

Shell Material Specification:

Qq-s-698, temper t5 federal specification single material response

Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

32 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.