# NSN 5935-00-485-5074

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-485-5074

Body	Style:	
------	--------	--

Straight shape, pc type

**Overall Length:** 

7.760 inches

**Overall Height:** 

0.670 inches

**Overall Width:** 

0.483 inches

**Unthreaded Mounting Hole Diameter:** 

0.127 inches

**Distance Between Mounting Facility Centers:** 

7.450 inches

**Board Accommodated Length:** 

6.900 inches single board

**Board Accommodated Width:** 

Between 0.055 inches and 0.070 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Switching contacts inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

350.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

490.0 single mating end single contact grouping

**Connector Locking Method:** 

Spring friction

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type ii, class 1 military specification 1st treatment response single mating end single contact grouping

# NSN 5935-00-485-5074

Electrical Receptacle Connector - Page 2 of 2



Terminal Ty
-------------

Printed circuit single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

# **Included Contact Quantity:**

136 single mating end single contact grouping

### **Included Contact Type:**

Bifurcated spring single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.136 gold grains, troy

#### **Precious Material:**

Gold

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

No

# Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.