NSN 5935-00-486-6109



Electrical Neceptacle Confidential - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5935-00-486-6109	
Body Style:	
Straight shape, flush mount	
Overall Length:	
0.954 inches	
Overall Height:	
2.000 inches	
Overall Width:	
2.047 inches	
Unthreaded Mounting Hole Diameter:	
0.140 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
1.437 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.720 inches	
Distance From Mounting Shoulder To Front Face:	
0.125 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
67 single mating end	
Contact Removability:	
Nonremovable single mating end all contact groupings	
Contact Maximum Current Rating In Amps:	
7.5 single mating end 2nd contact grouping	
Polarization Method:	
3 polarization posts	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded coupling ring	
Terminal Location:	
Back single mating end all contact groupings	

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Guide Design And Location:

Hexagon shape female post left-hand at 12 oclock and hexagon shape female post right-hand at 12 oclock

NSN 5935-00-486-6109

Electrical Receptacle Connector - Page 2 of 2



Shell Material:		
Aluminum alloy		
Shell Surface Treatment:		
Cadmium and chromate		
Included Contact Quantity:		
64 single mating end 2nd contact grouping		
Included Contact Type:		
Round socket single mating end all contact groupings		
Precious Material And Location:		
Contact surfaces gold and contact surfaces silver		
Precious Material And Weight:		
0.067 gold grains, troy and 0.067 silver grains, troy		
Precious Material:		
Gold and silver		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A039b0		