## NSN 5935-00-486-6816

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-486-6816
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, rectangular
Overall Length:
2.750 inches
Overall Height:
1.090 inches
Overall Width:
2.275 inches
Environmental Protection:
Heat resistant and pressure proof and vibration proof and watertight
Unthreaded Mounting Hole Diameter:
0.149 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.550 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.900 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
52 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1800.0 single mating end single contact grouping
Polarization Method:
Polarization boss
Shell Type:
Solid
Connector Locking Method:
Jackscrew
Thready Qty Per Inch (tpi):
28

Thread Size:

0.250 inches

## NSN 5935-00-486-6816

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Insert Material Specification:
Mil-m-19833, ty gdi-30f or mil-m-14, ty sdg-f military specification 1st material response single mating end and mil-m-19833, ty gdi-30f or
mil-m-14, ty sdg-f military specification 2nd material response single mating end and I-p-395 federal specification 3rd material response
single mating end
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0

Mil-std (military Standard): Mil-g-45204 spec.