

View Online at <https://aerobasegroup.com/nsn/5935-00-486-7014>

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.260 inches

**Overall Height:**

1.015 inches

**Overall Width:**

4.325 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.558 inches and 0.566 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 3.871 inches and 3.879 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.630 inches and 0.645 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

101 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

200.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

101 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Post spring mounted

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.101 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.