

View Online at <https://aerobasegroup.com/nsn/5935-00-488-3269>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Height:**

Between 0.682 inches and 0.692 inches

**Overall Width:**

Between 0.682 inches and 0.692 inches

**Unthreaded Mounting Hole Diameter:**

0.099 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.496 inches and 0.504 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.496 inches and 0.504 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.605 inches and 0.645 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Maximum Frequency Rating:**

4000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.099 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.