Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-488-3385

# **Body Style:**

Straight shape, external coupling

**Overall Length:** 

1.843 inches

# **Overall Height:**

1.510 inches

# **Overall Width:**

1.510 inches

Threaded Device Type:

Back shell and coupling facility

### Mating End Quantity:

1

### Contact Removability:

Removable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

# Insert Position In Deg:

0.0

#### Shell Type:

Solid

### **Connector Locking Method:**

Externally threaded shell

### **Included Contact Quantity:**

4 single mating end single contact grouping

### **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms3472 government standard

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A039b0



Mil-std (military Standard):

Mil-c-26482 spec.