Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-488-4719

## **Body Style:** Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.678 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 36w4 single mating end **Contact Removability:** Removable single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1250.0 single mating end 1st contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Cadmium **Insert Material Specification:**

L-p-395, type 1 federal specification single material response single mating end



**Included Contact Quantity:** 32 single mating end 1st contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.032 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A039b0

---