## NSN 5935-00-488-5806

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-488-5806

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

Between 2.747 inches and 2.763 inches

Overall Width:

0.248 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.096 inches and 0.101 inches

**Distance Between Mounting Facility Centers:** 

2.465 inches

**Board Accommodated Length:** 

1.800 inches single board

**Board Accommodated Width:** 

Between 0.068 inches and 0.072 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

48 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Special Features:** 

Polarizing pins position at 2 and 32

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-488-5806

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.048 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.