## NSN 5935-00-488-7015

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-488-7015 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/strain relief **Overall Length:** Between 2.922 inches and 3.016 inches **Overall Diameter:** Between 2.546 inches and 2.578 inches **Cable Entrance Diameter:** Between 1.046 inches and 1.078 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Ik-m7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 60.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp Thread Length: 0.516 inches Thready Qty Per Inch (tpi): **Thread Size:** 2.312 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## **NSN 5935-00-488-7015**Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.007 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0