

View Online at https://aerobasegroup.com/nsn/5935-00-488-7185

## **Thread Class:** 2a and 2b and 2a **Thread Direction: Right-hand Body Style:** Straight shape **Overall Length:** 2.719 inches **Overall Width:** 0.875 inches **Environmental Protection:** Heat resistant and moisture resistant and pressure proof and salt water resistant and vibration resistant and watertight **Distance Between Mounting Facility Centers:** 2.282 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 50 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40 **Thread Size:** 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end Shell Guide Type And Location Designator: B pin **Thread Series Designator:**

Unc

Electrical Receptacle Connector Body - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.