NSN 5935-00-489-1365

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-489-1365

Body Style:

Straight edge type w/mounting flange

Overall Length:

7.781 inches

Overall Height:

Between 0.431 inches and 0.476 inches

Overall Width:

Between 0.280 inches and 0.406 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.119 inches

Distance Between Mounting Facility Centers:

Between 7.304 inches and 7.336 inches

Board Accommodated Length:

6.862 inches single board and 6.882 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

43 single mating end single contact grouping

NSN 5935-00-489-1365

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Bifurcated accordian leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.043 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/1 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.