

View Online at <https://aerobasegroup.com/nsn/5935-00-489-1384>

**Body Style:**

Straight shape, flange mount, external coupling

**Overall Length:**

1.032 inches

**Overall Height:**

1.234 inches

**Overall Width:**

1.234 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.970 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.970 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.317 inches and 0.322 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16-99 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 95.0 and 132.0 and 232.0 and 260.0

**Shell Type:**

Potting

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Potting type

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Included Contact Quantity:**

21 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.031 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms27472 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.