NSN 5935-00-490-3725

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-490-3725

Body Style:

Straight shape threaded

Overall Length:

0.828 inches

Overall Diameter:

Between 0.953 inches and 0.985 inches

Environmental Protection:

Salt water resistant and vibration resistant and moisture resistant

Distance From Mounting Shoulder To Front Face:

Between 0.411 inches and 0.442 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Iron

Shell Surface Treatment:

Tin

Shell Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

NSN 5935-00-490-3725

A039b0

Mil-std (military Standard):

Mil-t-10727 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
19 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Soldered to panel
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.019 gold grains, troy and 0.019 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: