## NSN 5935-00-490-5146

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-490-5146

Thread Direction: Right-hand Body Style: Straight shape Overall Length: 1.250 inches Overall Height: 0.797 inches Overall Width: 0.438 inches Distance Between Mounting Facility Centers: 0.937 inches Threaded Device Type: Mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 14 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Body Style: Straight shape Overall Length: 1.250 inches Overall Height: 0.797 inches Overall Width: 0.438 inches Distance Between Mounting Facility Centers: 0.937 inches Threaded Device Type: Mounting stud Mating End Quantity: 1 Contact Position Arrangement Style: 14 single mating end Contact Removability: Nonremovable single mating end single contact grouping
Straight shape  Overall Length:  1.250 inches  Overall Height:  0.797 inches  Overall Width:  0.438 inches  Distance Between Mounting Facility Centers:  0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Overall Length:  1.250 inches  Overall Height:  0.797 inches  Overall Width:  0.438 inches  Distance Between Mounting Facility Centers:  0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
1.250 inches  Overall Height: 0.797 inches  Overall Width: 0.438 inches  Distance Between Mounting Facility Centers: 0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity: 1  Contact Position Arrangement Style: 14 single mating end  Contact Removability: Nonremovable single mating end single contact grouping
Overall Height:  0.797 inches  Overall Width:  0.438 inches  Distance Between Mounting Facility Centers:  0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
0.797 inches  Overall Width: 0.438 inches  Distance Between Mounting Facility Centers: 0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity: 1  Contact Position Arrangement Style: 14 single mating end  Contact Removability: Nonremovable single mating end single contact grouping
Overall Width:  0.438 inches  Distance Between Mounting Facility Centers:  0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
0.438 inches  Distance Between Mounting Facility Centers: 0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity: 1  Contact Position Arrangement Style: 14 single mating end  Contact Removability: Nonremovable single mating end single contact grouping
Distance Between Mounting Facility Centers:  0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
0.937 inches  Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Threaded Device Type:  Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Mounting stud  Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Mating End Quantity:  1  Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Contact Position Arrangement Style:  14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
14 single mating end  Contact Removability:  Nonremovable single mating end single contact grouping
Contact Removability:  Nonremovable single mating end single contact grouping
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1700.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.265 inches
0.265 inches Thread Size:
Thread Size:
Thread Size: 0.112 inches
Thread Size: 0.112 inches Terminal Location:

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-490-5146

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0