Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-490-5207

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, side opening w/clamp
Overall Length:
3.346 inches
Overall Height:
2.593 inches
Overall Width:
Between 0.870 inches and 0.880 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Cable Entrance Diameter:
0.546 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Hood, side opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## NSN 5935-00-490-5207

Electrical Plug Connector - Page 2 of 2



Insert Material:	
	halate single mating end
	e Treatment Specification:
	e 1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:	
	ing end single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Tr	reatment:
Cadmium	
Shell Surface Tr	reatment Specification:
Qq-p-416 type 2	, cl 1 federal specification single treatment response
Insert Material S	Specification:
Mil-m-14 ty sdg-f	military specification single material response single mating end
Shell Guide Typ	e And Location Designator:
B slot	
Included Contac	ct Quantity:
50 single mating	end single contact grouping
Included Contac	ct Type:
Round socket sir	ngle mating end single contact grouping
Precious Materi	al And Location:
Contact surfaces	gold
Precious Materi	al And Weight:
0.050 gold grains	s, troy
Precious Materi	al:
Gold	
Thread Series D	esignator:
Unc and unc	
Shelf Life:	
N/a	
Unit Of Measure	
Demilitarization	:
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
Mil-g-45294 spec	