Electrical Connector Guide - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-490-8810

| Thread Class:         |  |
|-----------------------|--|
| 2a                    |  |
| Thread Direction:     |  |
| Right-hand            |  |
| Furnished Items:      |  |
| Washer                |  |
| Overall Length:       |  |
| Between 0.765 inch    | nes and 0.797 inches   |
| Body Diameter:        |  |
| 0.190 inches          |  |
| Mounting Facility     | Type And Quantity:   |
| 1 threaded stud       |  |
| Thready Qty Per I     | nch (tpi):   |
| 40                    |  |
| Thread Size:          |  |
| 0.112 inches          |  |
| Special Features:     |  |
| Self locking nut with | n nylon insert supplied with part  |
| Material:             |  |
| Steel, corrosion re   | sisting  |
| Material:             |  |
| Stainless steel       |  |
| Surface Treatmen      | t:   |
| Passivate             |  |
| Style Designator:     |  |
| Socket w/groove       |  |
| Surface Treatmen      | t:   |
| Passivated            |  |
| Test Data Docume      | ent:   |
| 81349-mil-c-28748     | specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes c    | ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and     | performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Des     | signator:  |
| Unc                   |  |
| Specification Data    |  |
| 96906-ms18197 gc      | vernment standard  |
| Shelf Life:           |  |
| N/a                   |  |
| Unit Of Measure:      |  |
|                       |  |
| Demilitarization:     |  |
| No                    |  |
| Fiig:                 |  |
| A10100                |  |

Electrical Connector Guide - Page 2 of 2

Mil-std (military Standard):

Mil-c-28748 spec.

