NSN 5935-00-491-3891

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-491-3891

Body Style: Straight shape, external coupling **Overall Length:** 1.709 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.556 inches and 0.587 inches **Mating End Quantity: Contact Position Arrangement Style:** 22-41 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 39.0 Shell Type: **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and copper single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

NSN 5935-00-491-3891

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 27 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contract surfaces gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-26482 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |