Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-491-6724

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.823 inches |
| Overall Height: |
| Between 1.074 inches and 1.114 inches |
| Overall Width: |
| Between 1.074 inches and 1.114 inches |
| Environmental Protection: |
| Moisture resistant and pressure proof and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.148 inches and 0.154 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| Between 0.807 inches and 0.817 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.807 inches and 0.817 inches |
| Distance From Mounting Shoulder To Front Face: |
| Between 0.750 inches and 0.766 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 12s-3 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| |



Connector Locking Method: Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy Shell Surface Treatment: Cadmium Shell Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 2 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Furnished items - grommet **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.002 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A039b0