

View Online at <https://aerobasegroup.com/nsn/5935-00-492-1989>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Gray

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.922 inches and 1.000 inches

Mounting Bushing Length:

0.438 inches

Body Length:

0.563 inches

Overall Diameter:

0.410 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.080 inches single finger

Finger Accommodation Length:

0.563 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.250 inches

Thread Length:

0.375 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Type:

Turret

Material:

Copper alloy terminal

Material:
Plastic insulator

Precious Material And Location:
Contact surface gold

Precious Material And Weight:
0.001 gold grains, troy

Precious Material:
Gold

Surface Treatment:
Nickel bushing

Surface Treatment:
Nickel bushing

Test Data Document:
81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:
Unef

Specification Data:
81349-mil-c-39024/10 government specification

Shelf Life:
N/a

Unit Of Measure:
--

Demilitarization:
No

Fig:
A03400