Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-492-7929

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.799 inches

Overall Height:

0.594 inches

Overall Width:

0.250 inches

Distance Between Mounting Facility Centers:

Between 0.526 inches and 0.536 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

5 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping



| Solder w | ell single mating end single contact grouping |
|---------------------|---|
| Contact | Material Specification: |
| Qq-b-620 | 6, comp 22 federal specification single material response single mating end single contact grouping |
| Insert M | aterial Specification: |
| Mil-m-14 | , type sdg-f military specification single material response single mating end |
| Unable ⁻ | Γο Decode: |
| Unable to | o decode and unable to decode |
| Included | I Contact Quantity: |
| 5 single | mating end single contact grouping |
| Included | I Contact Type: |
| Round p | in single mating end single contact grouping |
| Special | Features: |
| Jackscre | w type-female and location-left handandjackscrew type-male and location-right hand |
| Precious | s Material And Location: |
| Contact | surfaces gold |
| Precious | s Material And Weight: |
| 0.005 go | ld grains, troy |
| Precious | s Material: |
| Gold | |
| Thread \$ | Series Designator: |
| Unc | |
| Shelf Lif | ie: |
| N/a | |
| Unit Of I | Measure: |
| | |
| Demilita | rization: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (| military Standard): |
| Mil-g-452 | 204 spec. |