NSN 5935-00-493-0462

Electrical Plug Connector - Page 1 of 2



462

| View Online at https://aerobasegroup.com/nsn/5935-00-493-04 |
|---|
| Body Style: |
| Angle shape, internal coupling |
| Overall Length: |
| 0.938 inches |
| Overall Height: |
| 1.024 inches |
| Overall Diameter: |
| 1.016 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 600.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 850.0 single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Connector Cable Strain Relief Method: |
| Potting type |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic epoxy single mating end and glass single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |

Cadmium

NSN 5935-00-493-0462

Electrical Plug Connector - Page 2 of 2



| In | clu | ded | Con | tact | Qı | ıantity | ,- |
|----|-----|-----|-----|------|----|---------|----|
| | uu | ucu | COL | ıacı | ωı | ıaııtıv | |

10 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Conact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0