NSN 5935-00-493-0465

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-493-0465

Body Style: Straight shape **Overall Length:** Between 2.620 inches and 2.650 inches **Overall Height:** 0.708 inches **Overall Width:** Between 0.590 inches and 0.620 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Metal

Nickel

Shell Surface Treatment:

NSN 5935-00-493-0465

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Mil-c-26074, class 3 or 4, grade b military specification single treatment response

Insert Material Specification:

Mil-m-14, type sdg-f military specification all material responses single mating end or mil-m-24519, type gpt-30f or type get-30f military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-24308/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.